



Model AG660 Series

Suction (PSIG)	Gas Volume Flow (mcf/d)											
	1	2	3	4	5	6	7	8	9	10	11	12
400	66.6	133.3	199.9	266.5	333.1	399.8	466.4	533.0	599.7	666.3	732.9	799.5
390	65.0	130.0	195.1	260.1	325.1	390.1	455.1	520.2	585.2	650.2	715.2	780.2
380	63.4	126.8	190.2	253.6	317.0	380.5	443.9	507.3	570.7	634.1	697.5	760.9
370	61.8	123.6	185.4	247.2	309.0	370.8	432.6	494.4	556.2	618.0	679.8	741.6
360	60.2	120.4	180.6	240.8	301.0	361.1	421.3	481.5	541.7	601.9	662.1	722.3
350	58.6	117.2	175.7	234.3	292.9	351.5	410.1	468.7	527.2	585.8	644.4	703.0
340	57.0	113.9	170.9	227.9	284.9	341.8	398.8	455.8	512.7	569.7	626.7	683.7
330	55.4	110.7	166.1	221.5	276.8	332.2	387.5	442.9	498.3	553.6	609.0	664.4
320	53.8	107.5	161.3	215.0	268.8	322.5	376.3	430.0	483.8	537.5	591.3	645.0
310	52.1	104.3	156.4	208.6	260.7	312.9	365.0	417.2	469.3	521.4	573.6	625.7
300	50.5	101.1	151.6	202.1	252.7	303.2	353.7	404.3	454.8	505.3	555.9	606.4
290	48.9	97.9	146.8	195.7	244.6	293.6	342.5	391.4	440.3	489.3	538.2	587.1
280	47.3	94.6	141.9	189.3	236.6	283.9	331.2	378.5	425.8	473.2	520.5	567.8
270	45.7	91.4	137.1	182.8	228.5	274.2	319.9	365.7	411.4	457.1	502.8	548.5
260	44.1	88.2	132.3	176.4	220.5	264.6	308.7	352.8	396.9	441.0	485.1	529.2
250	42.5	85.0	127.5	170.0	212.4	254.9	297.4	339.9	382.4	424.9	467.4	509.9
240	40.9	81.8	122.6	163.5	204.4	245.3	286.1	327.0	367.9	408.8	449.7	490.5
230	39.3	78.5	117.8	157.1	196.3	235.6	274.9	314.2	353.4	392.7	432.0	471.2
220	37.7	75.3	113.0	150.6	188.3	226.0	263.6	301.3	338.9	376.6	414.3	451.9
210	36.1	72.1	108.2	144.2	180.3	216.3	252.4	288.4	324.5	360.5	396.6	432.6
200	34.4	68.9	103.3	137.8	172.2	206.6	241.1	275.5	310.0	344.4	378.8	413.3
190	32.8	65.7	98.5	131.3	164.2	197.0	229.8	262.7	295.5	328.3	361.1	394.0
180	31.2	62.4	93.7	124.9	156.1	187.3	218.6	249.8	281.0	312.2	343.4	374.7
170	29.6	59.2	88.8	118.5	148.1	177.7	207.3	236.9	266.5	296.1	325.7	355.4
160	28.0	56.0	84.0	112.0	140.0	168.0	196.0	224.0	252.0	280.0	308.0	336.0
150	26.4	52.8	79.2	105.6	132.0	158.4	184.8	211.2	237.5	263.9	290.3	316.7
140	24.8	49.6	74.4	99.1	123.9	148.7	173.5	198.3	223.1	247.8	272.6	297.4
130	23.2	46.4	69.5	92.7	115.9	139.1	162.2	185.4	208.6	231.8	254.9	278.1
120	21.6	43.1	64.7	86.3	107.8	129.4	151.0	172.5	194.1	215.7	237.2	258.8
110	20.0	39.9	59.9	79.8	99.8	119.7	139.7	159.7	179.6	199.6	219.5	239.5
100	18.3	36.7	55.0	73.4	91.7	110.1	128.4	146.8	165.1	183.5	201.8	220.2
90	16.7	33.5	50.2	67.0	83.7	100.4	117.2	133.9	150.6	167.4	184.1	200.9
80	15.1	30.3	45.4	60.5	75.6	90.8	105.9	121.0	136.2	151.3	166.4	181.5
70	13.5	27.0	40.6	54.1	67.6	81.1	94.6	108.2	121.7	135.2	148.7	162.2
60	11.9	23.8	35.7	47.6	59.5	71.5	83.4	95.3	107.2	119.1	131.0	142.9
50	10.3	20.6	30.9	41.2	51.5	61.8	72.1	82.4	92.7	103.0	113.3	123.6
40	8.7	17.4	26.1	34.8	43.5	52.1	60.8	69.5	78.2	86.9	95.6	104.3
30	7.1	14.2	21.2	28.3	35.4	42.5	49.6	56.7	63.7	70.8	77.9	85.0
20	5.5	10.9	16.4	21.9	27.4	32.8	38.3	43.8	49.2	54.7	60.2	65.7
10	3.9	7.7	11.6	15.5	19.3	23.2	27.0	30.9	34.8	38.6	42.5	46.4
0	2.3	4.5	6.8	9.0	11.3	13.5	15.8	18.0	20.3	22.5	24.8	27.0
Strokes per minute	1	2	3	4	5	6	7	8	9	10	11	12

The ANNUGAS PRODUCTION ENHANCER® is a Walking Beam Gas Compressor in which the preferred mounting location is between the gear box and back samson post of the pumping unit but can be mounted in front of the samson post. Since the pumping unit is the driver of the ANNUGAS PRODUCTION ENHANCER®, flow line (discharge) pressure will be the determining factor of which model is selected for each application. To limit pumping unit damages due to high rod loads from the ANNUGAS PRODUCTION ENHANCER® discharge pressures are limited. For more information, go to the technical link on our website www.annugas.com