



Model AG860 Series

Suction (PSIG)	Gas Volume Flow (mcf/d)											
	1	2	3	4	5	6	7	8	9	10	11	12
225	71.3	142.7	214.0	285.3	356.6	428.0	499.3	570.6	641.9	713.3	784.6	855.9
220	69.8	139.7	209.5	279.3	349.2	419.0	488.8	558.7	628.5	698.3	768.2	838.0
210	66.9	133.7	200.6	267.4	334.3	401.1	468.0	534.8	601.7	668.5	735.4	802.2
200	63.9	127.7	191.6	255.5	319.3	383.2	447.1	510.9	574.8	638.7	702.5	766.4
190	60.9	121.8	182.6	243.5	304.4	365.3	426.2	487.1	547.9	608.8	669.7	730.6
180	57.9	115.8	173.7	231.6	289.5	347.4	405.3	463.2	521.1	579.0	636.9	694.8
170	54.9	109.8	164.7	219.7	274.6	329.5	384.4	439.3	494.2	549.1	604.0	659.0
160	51.9	103.9	155.8	207.7	259.6	311.6	363.5	415.4	467.4	519.3	571.2	623.1
150	48.9	97.9	146.8	195.8	244.7	293.7	342.6	391.6	440.5	489.4	538.4	587.3
140	46.0	91.9	137.9	183.8	229.8	275.8	321.7	367.7	413.6	459.6	505.6	551.5
130	43.0	86.0	128.9	171.9	214.9	257.9	300.8	343.8	386.8	429.8	472.7	515.7
120	40.0	80.0	120.0	160.0	200.0	239.9	279.9	319.9	359.9	399.9	439.9	479.9
110	37.0	74.0	111.0	148.0	185.0	222.0	259.0	296.1	333.1	370.1	407.1	444.1
100	34.0	68.0	102.1	136.1	170.1	204.1	238.2	272.2	306.2	340.2	374.2	408.3
90	31.0	62.1	93.1	124.2	155.2	186.2	217.3	248.3	279.3	310.4	341.4	372.5
80	28.1	56.1	84.2	112.2	140.3	168.3	196.4	224.4	252.5	280.5	308.6	336.6
70	25.1	50.1	75.2	100.3	125.3	150.4	175.5	200.6	225.6	250.7	275.8	300.8
60	22.1	44.2	66.3	88.3	110.4	132.5	154.6	176.7	198.8	220.8	242.9	265.0
50	19.1	38.2	57.3	76.4	95.5	114.6	133.7	152.8	171.9	191.0	210.1	229.2
40	16.1	32.2	48.3	64.5	80.6	96.7	112.8	128.9	145.0	161.2	177.3	193.4
30	13.1	26.3	39.4	52.5	65.7	78.8	91.9	105.1	118.2	131.3	144.4	157.6
20	10.1	20.3	30.4	40.6	50.7	60.9	71.0	81.2	91.3	101.5	111.6	121.8
10	7.2	14.3	21.5	28.7	35.8	43.0	50.1	57.3	64.5	71.6	78.8	86.0
0	4.2	8.4	12.5	16.7	20.9	25.1	29.2	33.4	37.6	41.8	46.0	50.1
Strokes per minute	1	2	3	4	5	6	7	8	9	10	11	12

The ANNUGAS PRODUCTION ENHANCER® is a Walking Beam Gas Compressor in which the preferred mounting location is between the gear box and back samson post of the pumping unit but can be mounted in front of the samson post. Since the pumping unit is the driver of the ANNUGAS PRODUCTION ENHANCER®, flow line (discharge) pressure will be the determining factor of which model is selected for each application. To limit pumping unit damages due to high rod loads from the ANNUGAS PRODUCTION ENHANCER® discharge pressures are limited. For more information, go to the technical link on our website www.annugas.com