



Model AG560 Series

Suction (PSIG)	Gas Volume Flow (mcf/d)											
	1	2	3	4	5	6	7	8	9	10	11	12
560	61.5	123.1	184.6	246.1	307.6	369.2	430.7	492.2	553.7	615.3	676.8	738.3
540	59.4	118.8	178.1	237.5	296.9	356.3	415.7	475.1	534.4	593.8	653.2	712.6
520	57.2	114.5	171.7	229.0	286.2	343.4	400.7	457.9	515.1	572.4	629.6	686.9
500	55.1	110.2	165.3	220.4	275.5	330.6	385.7	440.8	495.8	550.9	606.0	661.1
480	53.0	105.9	158.9	211.8	264.8	317.7	370.7	423.6	476.6	529.5	582.5	635.4
460	50.8	101.6	152.4	203.2	254.0	304.8	355.6	406.5	457.3	508.1	558.9	609.7
440	48.7	97.3	146.0	194.7	243.3	292.0	340.6	389.3	438.0	486.6	535.3	584.0
420	46.5	93.0	139.6	186.1	232.6	279.1	325.6	372.2	418.7	465.2	511.7	558.2
400	44.4	88.8	133.1	177.5	221.9	266.3	310.6	355.0	399.4	443.8	488.1	532.5
380	42.2	84.5	126.7	168.9	211.2	253.4	295.6	337.9	380.1	422.3	464.6	506.8
360	40.1	80.2	120.3	160.4	200.4	240.5	280.6	320.7	360.8	400.9	441.0	481.1
340	37.9	75.9	113.8	151.8	189.7	227.7	265.6	303.6	341.5	379.4	417.4	455.3
320	35.8	71.6	107.4	143.2	179.0	214.8	250.6	286.4	322.2	358.0	393.8	429.6
300	33.7	67.3	101.0	134.6	168.3	201.9	235.6	269.3	302.9	336.6	370.2	403.9
280	31.5	63.0	94.5	126.1	157.6	189.1	220.6	252.1	283.6	315.1	346.6	378.2
260	29.4	58.7	88.1	117.5	146.8	176.2	205.6	235.0	264.3	293.7	323.1	352.4
240	27.2	54.5	81.7	108.9	136.1	163.4	190.6	217.8	245.0	272.3	299.5	326.7
220	25.1	50.2	75.2	100.3	125.4	150.5	175.6	200.7	225.7	250.8	275.9	301.0
200	22.9	45.9	68.8	91.8	114.7	137.6	160.6	183.5	206.4	229.4	252.3	275.3
180	20.8	41.6	62.4	83.2	104.0	124.8	145.6	166.4	187.1	207.9	228.7	249.5
160	18.7	37.3	56.0	74.6	93.3	111.9	130.6	149.2	167.9	186.5	205.2	223.8
140	16.5	33.0	49.5	66.0	82.5	99.0	115.5	132.1	148.6	165.1	181.6	198.1
120	14.4	28.7	43.1	57.5	71.8	86.2	100.5	114.9	129.3	143.6	158.0	172.4
100	12.2	24.4	36.7	48.9	61.1	73.3	85.5	97.8	110.0	122.2	134.4	146.6
80	10.1	20.2	30.2	40.3	50.4	60.5	70.5	80.6	90.7	100.8	110.8	120.9
60	7.9	15.9	23.8	31.7	39.7	47.6	55.5	63.5	71.4	79.3	87.3	95.2
40	5.8	11.6	17.4	23.2	28.9	34.7	40.5	46.3	52.1	57.9	63.7	69.5
20	3.6	7.3	10.9	14.6	18.2	21.9	25.5	29.2	32.8	36.4	40.1	43.7
0	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	16.5	18.0
Strokes per minute	1	2	3	4	5	6	7	8	9	10	11	12

The ANNUGAS PRODUCTION ENHANCER® is a Walking Beam Gas Compressor in which the preferred mounting location is between the gear box and back samson post of the pumping unit but can be mounted in front of the samson post. Since the pumping unit is the driver of the ANNUGAS PRODUCTION ENHANCER®, flow line (discharge) pressure will be the determining factor of which model is selected for each application. To limit pumping unit damages due to high rod loads from the ANNUGAS PRODUCTION ENHANCER® discharge pressures are limited. For more information, go to the technical link on our website www.annugas.com