



### Model AG724 Series

Suction (PSIG)	Gas Volume Flow (mcf/d)											
	1	2	3	4	5	6	7	8	9	10	11	12
300	28.3	56.6	84.9	113.2	141.5	169.8	198.1	226.4	254.7	283.0	311.3	339.6
290	27.4	54.8	82.2	109.6	137.0	164.4	191.8	219.2	246.6	274.0	301.4	328.8
280	26.5	53.0	79.5	106.0	132.5	159.0	185.5	212.0	238.5	265.0	291.5	318.0
270	25.6	51.2	76.8	102.4	128.0	153.6	179.2	204.8	230.4	256.0	281.6	307.1
260	24.7	49.4	74.1	98.8	123.5	148.2	172.9	197.6	222.2	246.9	271.6	296.3
250	23.8	47.6	71.4	95.2	119.0	142.8	166.6	190.3	214.1	237.9	261.7	285.5
240	22.9	45.8	68.7	91.6	114.5	137.4	160.2	183.1	206.0	228.9	251.8	274.7
230	22.0	44.0	66.0	88.0	110.0	131.9	153.9	175.9	197.9	219.9	241.9	263.9
220	21.1	42.2	63.3	84.4	105.4	126.5	147.6	168.7	189.8	210.9	232.0	253.1
210	20.2	40.4	60.6	80.8	100.9	121.1	141.3	161.5	181.7	201.9	222.1	242.3
200	19.3	38.6	57.9	77.1	96.4	115.7	135.0	154.3	173.6	192.9	212.2	231.4
190	18.4	36.8	55.2	73.5	91.9	110.3	128.7	147.1	165.5	183.9	202.2	220.6
180	17.5	35.0	52.5	69.9	87.4	104.9	122.4	139.9	157.4	174.8	192.3	209.8
170	16.6	33.2	49.7	66.3	82.9	99.5	116.1	132.7	149.2	165.8	182.4	199.0
160	15.7	31.4	47.0	62.7	78.4	94.1	109.8	125.5	141.1	156.8	172.5	188.2
150	14.8	29.6	44.3	59.1	73.9	88.7	103.5	118.2	133.0	147.8	162.6	177.4
140	13.9	27.8	41.6	55.5	69.4	83.3	97.2	111.0	124.9	138.8	152.7	166.6
130	13.0	26.0	38.9	51.9	64.9	77.9	90.8	103.8	116.8	129.8	142.8	155.7
120	12.1	24.2	36.2	48.3	60.4	72.5	84.5	96.6	108.7	120.8	132.8	144.9
110	11.2	22.4	33.5	44.7	55.9	67.1	78.2	89.4	100.6	111.8	122.9	134.1
100	10.3	20.5	30.8	41.1	51.4	61.6	71.9	82.2	92.5	102.7	113.0	123.3
90	9.4	18.7	28.1	37.5	46.9	56.2	65.6	75.0	84.4	93.7	103.1	112.5
80	8.5	16.9	25.4	33.9	42.4	50.8	59.3	67.8	76.2	84.7	93.2	101.7
70	7.6	15.1	22.7	30.3	37.9	45.4	53.0	60.6	68.1	75.7	83.3	90.8
60	6.7	13.3	20.0	26.7	33.3	40.0	46.7	53.4	60.0	66.7	73.4	80.0
50	5.8	11.5	17.3	23.1	28.8	34.6	40.4	46.1	51.9	57.7	63.4	69.2
40	4.9	9.7	14.6	19.5	24.3	29.2	34.1	38.9	43.8	48.7	53.5	58.4
30	4.0	7.9	11.9	15.9	19.8	23.8	27.8	31.7	35.7	39.7	43.6	47.6
20	3.1	6.1	9.2	12.3	15.3	18.4	21.4	24.5	27.6	30.6	33.7	36.8
10	2.2	4.3	6.5	8.7	10.8	13.0	15.1	17.3	19.5	21.6	23.8	26.0
0	1.3	2.5	3.8	5.0	6.3	7.6	8.8	10.1	11.4	12.6	13.9	15.1
Strokes per minute	1	2	3	4	5	6	7	8	9	10	11	12

The ANNUGAS PRODUCTION ENHANCER® is a Walking Beam Gas Compressor in which the preferred mounting location is between the gear box and back samson post of the pumping unit but can be mounted in front of the samson post. Since the pumping unit is the driver of the ANNUGAS PRODUCTION ENHANCER®, flow line (discharge) pressure will be the determining factor of which model is selected for each application. To limit pumping unit damages due to high rod loads from the ANNUGAS PRODUCTION ENHANCER® discharge pressures are limited. For more information, go to the technical link on our website [www.annugas.com](http://www.annugas.com)