



Model AG760 Series

Suction (PSIG)	Gas Volume Flow (mcf/d)											
	1	2	3	4	5	6	7	8	9	10	11	12
300	70.7	141.5	212.2	283.0	353.7	424.5	495.2	566.0	636.7	707.5	778.2	849.0
290	68.5	137.0	205.5	274.0	342.5	411.0	479.5	548.0	616.5	685.0	753.4	821.9
280	66.2	132.5	198.7	265.0	331.2	397.5	463.7	529.9	596.2	662.4	728.7	794.9
270	64.0	128.0	192.0	256.0	319.9	383.9	447.9	511.9	575.9	639.9	703.9	767.9
260	61.7	123.5	185.2	246.9	308.7	370.4	432.1	493.9	555.6	617.4	679.1	740.8
250	59.5	119.0	178.4	237.9	297.4	356.9	416.4	475.9	535.3	594.8	654.3	713.8
240	57.2	114.5	171.7	228.9	286.1	343.4	400.6	457.8	515.1	572.3	629.5	686.8
230	55.0	110.0	164.9	219.9	274.9	329.9	384.8	439.8	494.8	549.8	604.7	659.7
220	52.7	105.4	158.2	210.9	263.6	316.3	369.1	421.8	474.5	527.2	580.0	632.7
210	50.5	100.9	151.4	201.9	252.4	302.8	353.3	403.8	454.2	504.7	555.2	605.6
200	48.2	96.4	144.7	192.9	241.1	289.3	337.5	385.7	434.0	482.2	530.4	578.6
190	46.0	91.9	137.9	183.9	229.8	275.8	321.7	367.7	413.7	459.6	505.6	551.6
180	43.7	87.4	131.1	174.8	218.6	262.3	306.0	349.7	393.4	437.1	480.8	524.5
170	41.5	82.9	124.4	165.8	207.3	248.7	290.2	331.7	373.1	414.6	456.0	497.5
160	39.2	78.4	117.6	156.8	196.0	235.2	274.4	313.6	352.8	392.0	431.2	470.5
150	37.0	73.9	110.9	147.8	184.8	221.7	258.7	295.6	332.6	369.5	406.5	443.4
140	34.7	69.4	104.1	138.8	173.5	208.2	242.9	277.6	312.3	347.0	381.7	416.4
130	32.4	64.9	97.3	129.8	162.2	194.7	227.1	259.6	292.0	324.5	356.9	389.3
120	30.2	60.4	90.6	120.8	151.0	181.2	211.3	241.5	271.7	301.9	332.1	362.3
110	27.9	55.9	83.8	111.8	139.7	167.6	195.6	223.5	251.4	279.4	307.3	335.3
100	25.7	51.4	77.1	102.7	128.4	154.1	179.8	205.5	231.2	256.9	282.5	308.2
90	23.4	46.9	70.3	93.7	117.2	140.6	164.0	187.5	210.9	234.3	257.8	281.2
80	21.2	42.4	63.5	84.7	105.9	127.1	148.3	169.4	190.6	211.8	233.0	254.2
70	18.9	37.9	56.8	75.7	94.6	113.6	132.5	151.4	170.3	189.3	208.2	227.1
60	16.7	33.3	50.0	66.7	83.4	100.0	116.7	133.4	150.1	166.7	183.4	200.1
50	14.4	28.8	43.3	57.7	72.1	86.5	100.9	115.4	129.8	144.2	158.6	173.0
40	12.2	24.3	36.5	48.7	60.8	73.0	85.2	97.3	109.5	121.7	133.8	146.0
30	9.9	19.8	29.7	39.7	49.6	59.5	69.4	79.3	89.2	99.1	109.1	119.0
20	7.7	15.3	23.0	30.6	38.3	46.0	53.6	61.3	68.9	76.6	84.3	91.9
10	5.4	10.8	16.2	21.6	27.0	32.4	37.9	43.3	48.7	54.1	59.5	64.9
0	3.2	6.3	9.5	12.6	15.8	18.9	22.1	25.2	28.4	31.5	34.7	37.9
Strokes per minute	1	2	3	4	5	6	7	8	9	10	11	12

The ANNUGAS PRODUCTION ENHANCER® is a Walking Beam Gas Compressor in which the preferred mounting location is between the gear box and back samson post of the pumping unit but can be mounted in front of the samson post. Since the pumping unit is the driver of the ANNUGAS PRODUCTION ENHANCER®, flow line (discharge) pressure will be the determining factor of which model is selected for each application. To limit pumping unit damages due to high rod loads from the ANNUGAS PRODUCTION ENHANCER® discharge pressures are limited. For more information, go to the technical link on our website www.annugas.com